

# Product Information

**Product Name \***

CC-Fönsterdrev

**Status**

Listed

**Product Category**

Products in Nordic Ecolabelled Buildings

**Product Subcategory**

Appendix 9: Declaration on excluded substances, nanoparticles and antibacterial additives in construction products, construction goods and materials

**Manufacturer Contact**

**Product Group**

900 Building materials

**Product Type**

Weatherproofing systems, tape and sealing strip

## Component for the Listed Material

**Listed products and materials**

Product Name	Manufacturer	Status	Product Type	GTIN	Material ID	Valid from	Valid to
--------------	--------------	--------	--------------	------	-------------	------------	----------

No records are available in this view

## Component for the Listed material

**Licence Products**

Status	Product Name	Product Type	Licence Product Status	Licence Nr.	Licence Version	Criteria Generation	Trade Name (SE)	Trade Name (NO)	Trade Name (DK)	Trade Name (FI)	Trade Name (IS)	Trade Name (O)
--------	--------------	--------------	------------------------	-------------	-----------------	---------------------	-----------------	-----------------	-----------------	-----------------	-----------------	----------------

No records are available in this view

<

>

**Valid from**

03-05-2017 16:32

**Listed Date**

03-05-2017 16:32

**Valid to**

31-12-2022

**Listed by**

Jacob Paulsen

## General

**Remarks (Reserved for Nordic Ecolabelling)****Add additional information of the product (Reserved for the Manufacturer)**

CC-Fönsterdrev består av finporig, impregnerad skumplast som är 30 mm tjock och som pressas samman till en tjocklek av 2 mm . CC-Fönsterdrev klipps i lagom längd och förs in i spalten mellan karm och sidostycke. Vid normal rumstemperatur expanderar remsan till sin fulla tjocklek på 1-3 timmar.

CC Expanding sealer consists of fine porous foam that is compressed to a thickness of 2 mm. Cut off the proper length and place it into the gap between the frame and the side piece. After 1-3 hours the sealer expands to its full thickness of 30 mm.

CC Window Drive is environmentally friendly and does not contain isocyanate \* Which means that the installer does not need to use protective clothing or make continuous medical examinations. Other advantages are that the sealer remains elastic and the window/door can be adjusted without any problems. Overall, you get significant time savings compared to conventional sealers

## Trade Name and Sales Agent

Sweden

**Marketed in SE** Yes No**Trade Name (SE)**

CC-Fönsterdrev

**GTIN (SE)**

7331316306085

**ID number (SE)**

Finland

**Marketed in FI**

Yes

No

**Trade Name (FI)**

CC-Ikkunatiiviste

**GTIN (FI)**

7331316306085

**ID number (FI)**

Norway

**Marketed in NO**

Yes

No

**Trade Name (NO)**

CC-Isolasjonsdrev

**GTIN (NO)**

7032940011276

**ID number (NO)**

Iceland

**Marketed in IS**

Yes

No

**Trade Name (IS)**

CC-Drevet

**GTIN (IS)**

**ID number (IS)**

Denmark

**Marketed in DK**

Yes

No

**Trade Name (DK)**

**GTIN (DK)**

**ID number (DK)**



English



**Trade Name (English)**

CC Expanding

All times (UTC+01:00) Brussels, Copenhagen, Madrid, Paris unless otherwise noted  
© 2020 Nordic Ecolabelling, All Rights Reserved ®  
3.8.0.0

